

A1 SOLVENT

DESCRIPTION

A1 SOLVENT can be applied to solvent-based concrete sealer to:

1. Allow moisture to release from sealed concrete. Roll, brush, or spray on to surface of solvent based acrylic sealer. Sealer will dry hard again within a few hours.
2. Dissolve bubbles in film by re-emulsifying sealer.
3. Clean up tools. Soak metal tools briefly, wipe clean, and allow to dry.
4. Thinner for sealer. Solvent will thin solvent based acrylic sealer. Add sealer to solvent 4:1 and stir for a minute.
5. Use **A1 SOLVENT** between sealing years to bring back shine.

FEATURES

★Hot Solvent acts fast ★Cuts through film build up ★Cleans tools

APPLICATION

Apply **A1 SOLVENT** with a roller, brush, or sprayer. Best results are achieved when the wash is done on a cool, overcast day. Avoid applying **A1 SOLVENT** in direct sunlight or hot weather. Sweep all dirt, debris, and loose sealer off the concrete to be treated. Pour the solvent into a metal or solvent-resistant paint tray and use a short-nap, solvent-resistant roller to apply **A1 SOLVENT** to the areas of sealer to be treated at a coverage rate of approximately 200 ft²/gallon. Use steady, even strokes to apply the solvent but do not "over roll" back and forth aggressively as this can cause bubbling. After a few minutes, **A1 SOLVENT** will re-wet the sealer, turning it back to its original liquid form. Sealer will dry hard again within a few hours. Allow 4 hours to dry before walking on and 48 hours before driving on surface.

HMIS

Health	2	Flammability	3
Reactivity	0	Protection	B

PRECAUTIONS

Flammable! Contains Petroleum distillates. Keep away from heat and flames. Use only with adequate ventilation. Avoid prolonged breathing of vapors and contact with skin. Keep out of eyes and mouth. WEAR RUBBER GLOVES AND SAFETY GLASSES. Keep container closed when not in use. In case of spill, absorb and dispose of in accordance with local applicable regulations. KEEP AWAY FROM CHILDREN!

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052